## NSN 4820-01-159-3272

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-159-3272

view Offilitie at https://aerobasegroup.com/hsh/4020-01-109-32
Flow Control Device:
Disk
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 2nd end
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
1.000 inches
Adjustable Pressure Range:
+33.0/+40.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
5.062 inches 1st end
Thickness:
0.438 inches 2nd end
First Connection Face To Centerline Distance:
3.469 inches
Bolt Hole Diameter:
0.562 inches 2nd end
Second Connection Face To Centerline Distance:
3.625 inches
Bolt Circle Diameter:
4.438 inches 2nd end
Flange Face Design:
Plain 2nd end
Material:
Nickel alloy seat
Material Specification:
Qq-n-281 federal specification single material response seat
Media For Which Designed:
Liquid, ingested single response
Style Designator:
Err-090

## NSN 4820-01-159-3272

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0