NSN 4820-01-161-2649

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-161-2649

| Thread Disastion |
|---|
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Renewable Seat Ring Type: |
| Retaining screw |
| Maximum Operating Temp: |
| 225.0 degrees fahrenheit single response |
| Connection Style: |
| G46b plain (pipe) all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded external pipe all ends |
| Maximum Operating Pressure: |
| 6000.0 pounds per square inch single response |
| Thread Size: |
| 0.375 inches all ends |
| Material: |
| Steel comp 316 stem |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Npt all ends |
| Furnished Items And Quantity: |
| 1 tailpiece and 1 nut |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |