# NSN 4820-01-163-1067

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-163-1067



## Flow Control Device:

Disk

Bonnet Type:

Inside spring

## **Bonnet Attachment Method:**

Bolted

## Maximum Operating Temp:

150.0 degrees fahrenheit single response

#### **End Application:**

Nimitz class cvn

#### Valve Operation Method:

Automatic

#### Flange Shape:

Round all ends

#### **Connection Type:**

Flange all ends

#### Valve Size:

2.000 inches

### Maximum Operating Pressure:

150.0 pounds per square inch single response

## **Opening Pressure Setting:**

86.0 pounds per square inch

## **Outside Diameter:**

6.000 inches all ends

#### Thickness:

0.500 inches all ends

## First Connection Face To Centerline Distance:

4.753 inches

## Second Connection Face To Centerline Distance:

4.753 inches

#### Flange Face Design:

Plain all ends

#### Material:

Copper alloy body

#### Style Designator:

Err-090

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 4820-01-163-1067

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

