

View Online at <https://aerobasegroup.com/nsn/4820-01-167-9446>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

265.0 degrees fahrenheit single response

**Connection Style:**

Plain (tube) 2nd end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 2nd end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

20 2nd end

**Maximum Operating Pressure:**

4000.0 pounds per square inch single response

**Thread Size:**

0.719 inches 1st end

**Special Features:**

End fittings per resistoflex dynatube r44090

**Material:**

Steel comp 630 flow control device

**Media For Which Designed:**

Nitrogen, gaseous single response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Uns 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530b0

**Mil-std (military Standard):**

Mil-s-5002 spec.