NSN 4820-01-168-5103

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-168-5103 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Connection Style:** External seat for gasket seal (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss 2nd end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Special Features:** One end is double threaded bulkhead per ms33657 Material: Aluminum alloy 2024 body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unjf 1st end Shelf Life: N/a

__

Unit Of Measure:

NSN 4820-01-168-5103

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.