## NSN 4820-01-170-9778

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-170-9778



## Flow Control Device:

Disk

Bonnet Type:

Inside screw

## **Bonnet Attachment Method:**

Threaded

### Maximum Operating Temp:

180.0 degrees fahrenheit single response

## Valve Operation Method:

Automatic

#### Flange Shape:

Round 2nd end

#### **Connection Type:**

Flange 1st end

#### Valve Size:

2.000 inches

#### Adjustable Pressure Range:

+90.0/+140.0 pounds per square inch

#### Maximum Operating Pressure:

300.0 pounds per square inch single response

### **Outside Diameter:**

8.250 inches 1st end

#### Thickness:

0.906 inches 1st end

## First Connection Face To Centerline Distance:

4.500 inches

## Second Connection Face To Centerline Distance:

4.125 inches

## Flange Face Design:

Plain 2nd end

#### Material:

Rubber butadiene-acrylonitrile class nbr flow control device

#### **Material Specification:**

Qq-n-281 federal specification single material response stem

#### Media For Which Designed:

Water, salt single response

#### Style Designator:

Err-090

### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 4820-01-170-9778

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

