## NSN 4820-01-170-9778

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-170-9778

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round 2nd end
Connection Type:
Flange 1st end
Valve Size:
2.000 inches
Adjustable Pressure Range:
+90.0/+140.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
8.250 inches 1st end
Thickness:
0.906 inches 1st end
First Connection Face To Centerline Distance:
4.500 inches
Second Connection Face To Centerline Distance:
4.125 inches
Flange Face Design:
Plain 2nd end
Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-170-9778

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0