

View Online at <https://aerobasegroup.com/nsn/4820-01-171-4260>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

3.000 inches

Outside Diameter:

7.500 inches all ends

Thickness:

0.938 inches all ends

First Connection Face To Centerline Distance:

4.750 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

4.750 inches

Bolt Circle Diameter:

6.000 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

5.000 inches all ends

Special Features:

Stop check internally

Material:

Steel uns j92800 body

Material Specification:

Mil p 17303 military specification single material response packing

Style Designator:

Err-090

Supplementary Features:

Uthis item has been reviewed for asbestos material; the current sources, 79342 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

spec.