NSN 4820-01-171-4393

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-171-4393

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+59.0/+72.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Opening Pressure Setting:
72.0 pounds per square inch
Outside Diameter:
7.500 inches all ends
Thickness:
0.437 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.750 inches
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem

NSN 4820-01-171-4393

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0