NSN 4820-01-172-6640

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-172-6640

Tion Control Bevice.
Disk
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+65.0/+100.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.688 inches 1st end
First Connection Face To Centerline Distance:
3.750 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
3.750 inches
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Plain all ends
Material:
Steel uns j03002 body
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-172-6640

Safety Relief Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0