

View Online at <https://aerobasegroup.com/nsn/4820-01-173-1161>

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Bolt Hole Quantity:

6 1st end

Connection Style:

G49c gasket seal (hose) 2nd end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Threaded external hose 2nd end

Maximum Operating Pressure:

280.0 pounds per square inch single response

Thread Size:

1.500 inches 2nd end

Outside Diameter:

5.062 inches 1st end

Thickness:

0.812 inches 1st end

Bolt Hole Diameter:

0.562 inches 1st end

Bolt Circle Diameter:

3.938 inches 1st end

Flange Face Design:

Plain 1st end

Material:

Plastic polytetrafluoroethylene packing

Media For Which Designed:

Water, fresh 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 80064 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Npsh 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0