NSN 4820-01-173-1166

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-173-1166 Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method: Bolted Bolt Hole Quantity:** 6 1st end **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 1.000 inches **Adjustable Pressure Range:** +59.0/+72.0 pounds per square inch **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Outside Diameter:** 5.562 inches 1st end Thickness: 0.438 inches all ends **First Connection Face To Centerline Distance:** 3.625 inches **Bolt Hole Diameter:** 0.562 inches all ends **Second Connection Face To Centerline Distance:** 3.469 inches **Bolt Circle Diameter:** 4.438 inches 1st end Flange Face Design: Plain all ends Material: Stainless steel stem **Style Designator:** Err-090 Shelf Life:

N/a

NSN 4820-01-173-1166

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0