

View Online at <https://aerobasegroup.com/nsn/4820-01-174-3485>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

5.000 inches

Outside Diameter:

10.000 inches all ends

Thickness:

0.875 inches all ends

First Connection Face To Centerline Distance:

7.250 inches

Bolt Hole Diameter:

0.875 inches all ends

Second Connection Face To Centerline Distance:

7.250 inches

Bolt Circle Diameter:

8.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

7.250 inches all ends

Material:

Steel uns j03002 bodysteel uns j03002 flow control device stainless steel seat steel comp 410 stem

Material Specification:

Astm a216 grade wcb assn standard single material response body astm a216 grade wcb assn standard single material response flow control device astm a182 grade f6 assn standard single material response seat astm aisi 410 assn standard single material response stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0