

NSN 4820-01-174-7106 Calibrated Flow Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-174-7106 **Body Material:** Aluminum **Body Style:** Tee Media For Which Designed: Hydraulic fluid, mil-h-5606 **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 3/4-16 unif First End Thread Class: 3b **First End Thread Direction:** Right-hand Second End Relationship With First End:

Identical

Third End Relationship With Preceding Ends:

Not identical with first or second end

Third End Connection Type:

Threaded internal boss

Third End Style Designator:

Gasket seal

Third End Thread Size And Series/type Designator:

9/16-18 unjf

Third End Thread Class:

3b

Third End Thread Direction:

Right-hand

Center To Center Distance:

0.970 inches

Flow Control Device:

Poppet

Flow Control Device Material:

Steel

End Connection Quantity:

3

Valve Discharge Flow Rate:

3.0 gallons per minute

Tempurature Rating:

Between -40.0 degrees fahrenheit and 175.0 degrees fahrenheit

NSN 4820-01-174-7106

Calibrated Flow Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100