

View Online at <https://aerobasegroup.com/nsn/4820-01-175-1076>

**Flow Control Device:**

Disk

**Disk Loading Method:**

Weight

**Bolt Hole Quantity:**

8 all ends

**Valve Operation Method:**

Automatic

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Mounting Position:**

Horizontal or vertical

**Valve Size:**

2.000 inches

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Outside Diameter:**

6.000 inches all ends

**Face To Face Distance:**

8.000 inches

**Thickness:**

0.562 inches all ends

**Bolt Hole Diameter:**

0.750 inches all ends

**Bolt Circle Diameter:**

4.750 inches all ends

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.062 inches all ends

**Raised Face Diameter:**

3.625 inches all ends

**Special Features:**

0.062 in. Thick graphited nonb asbestos gasket is included for cover tightness

**Material:**

Steel uns j92800 body

**Material Specification:**

Astm a217 grade ca15 assn standard single material response flow control device

**Style Designator:**

Straight through flanged ends

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 79342 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530b0