

View Online at <https://aerobasegroup.com/nsn/4820-01-175-1076>

Flow Control Device:

Disk

Disk Loading Method:

Weight

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Valve Size:

2.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Face To Face Distance:

8.000 inches

Thickness:

0.562 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

3.625 inches all ends

Special Features:

0.062 in. Thick graphited nonb asbestos gasket is included for cover tightness

Material:

Steel uns j92800 body

Material Specification:

Astm a217 grade ca15 assn standard single material response flow control device

Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 79342 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0