

View Online at <https://aerobasegroup.com/nsn/4820-01-177-8459>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.500 inches

Adjustable Pressure Range:

+171.0/+209.0 pounds per square inch

Opening Pressure Setting:

190.0 pounds per square inch

Outside Diameter:

4.250 inches 1st end

Thickness:

0.375 inches 1st end

First Connection Face To Centerline Distance:

3.438 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

3.438 inches

Bolt Circle Diameter:

3.125 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.375 inches all ends

Material:

Stainless steel stem

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

B grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.