## NSN 4820-01-179-6219

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-179-6219

Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
2.500 inches
Adjustable Pressure Range:
+135.0/+165.0 pounds per square inch
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.688 inches 1st end
First Connection Face To Centerline Distance:
6.000 inches
Bolt Hole Diameter:
0.625 inches 1st end
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Plain 2nd end
Material:
Stainless steel stem
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a

## NSN 4820-01-179-6219

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0