NSN 4820-01-180-1752

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-180-1752

Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Union Maximum Operating Temp: 406.0 degrees fahrenheit single response	
0.750 inches all ends Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Union Maximum Operating Temp: 406.0 degrees fahrenheit single response Connection Style:	
Disk Bonnet Type: Inside screw Bonnet Attachment Method: Union Maximum Operating Temp: 406.0 degrees fahrenheit single response	
Bonnet Type: Inside screw Bonnet Attachment Method: Union Maximum Operating Temp: 406.0 degrees fahrenheit single response	
Inside screw Bonnet Attachment Method: Union Maximum Operating Temp: 406.0 degrees fahrenheit single response	
Bonnet Attachment Method: Union Maximum Operating Temp: 406.0 degrees fahrenheit single response	
Union Maximum Operating Temp: 406.0 degrees fahrenheit single response	
Maximum Operating Temp: 406.0 degrees fahrenheit single response	
406.0 degrees fahrenheit single response	
Connection Style:	
Streamlined with one brazing ring all ends	
Valve Operation Method:	
Manual	
Connection Type:	
Unthreaded internal pipe all ends	
Features Provided:	
Bonnet packing	
Maximum Operating Pressure:	
300.0 pounds per square inch 2nd response	
Material:	
Silicon stem and copper alloy stem	
Media For Which Designed:	
Water-oil-gas 2nd response	
Style Designator:	
Err-090	
Supplementary Features:	
This item has been reviewed for asbestos material. The current approved source 21268 has indicated their part number contained asbe	stos
prior to 1984. They continue to manufacture the same part number without asbestos material after 1984	
Furnished Items And Quantity:	
1 handwheel	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A046b0	