## NSN 4820-01-180-8478

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-180-8478

Pipe Size Accommodated:
0.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+535.0/+755.0 pounds per square inch
Maximum Operating Procesures
Maximum Operating Pressure:
1500.0 pounds per square inch single response
1500.0 pounds per square inch single response
1500.0 pounds per square inch single response  Material:
1500.0 pounds per square inch single response  Material:  Nickel alloy stem
1500.0 pounds per square inch single response  Material:  Nickel alloy stem  Style Designator:
1500.0 pounds per square inch single response  Material:  Nickel alloy stem  Style Designator:  Err-090
1500.0 pounds per square inch single response  Material:  Nickel alloy stem  Style Designator:  Err-090  Shelf Life:
1500.0 pounds per square inch single response  Material:  Nickel alloy stem  Style Designator:  Err-090  Shelf Life:  N/a
1500.0 pounds per square inch single response  Material: Nickel alloy stem  Style Designator: Err-090  Shelf Life: N/a  Unit Of Measure:
1500.0 pounds per square inch single response  Material: Nickel alloy stem  Style Designator: Err-090  Shelf Life: N/a Unit Of Measure:
1500.0 pounds per square inch single response  Material: Nickel alloy stem  Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: Demilitarization:
1500.0 pounds per square inch single response  Material: Nickel alloy stem  Style Designator: Err-090  Shelf Life: N/a  Unit Of Measure: Demilitarization: No
1500.0 pounds per square inch single response  Material: Nickel alloy stem  Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: