NSN 4820-01-182-5129

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-182-5129

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-65.0 degrees fahrenheit
End Application:
Helicopter, apache ah-64
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.875 inches all ends
Seat Angle:
12.0 degrees all ends
Outside Diameter Tube Accommodated:
0.625 inches all ends
Special Features:
Cracking pressure is rated at 4 inches h20 (water)
Material:
Aluminum alloy
Media For Which Designed:
Fuel/oil, hydrocarbon 1st response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unjf all ends

NSN 4820-01-182-5129

Check Valve - Page 2 of 2



-			 	
•	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.