## NSN 4820-01-184-2732

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-184-2732

I IOW COILL	of Device:				
Disk					
Bonnet Typ	De:				
Inside sprin	g				
Bonnet Attachment Method:					
Union					
Disk Loadi	ng Method:				
Spring					
Bolt Hole C	luantity:				
4 all ends					
Valve Oper	ation Method:				
Automatic					
Flange Sha	ipe:				
Round with	holes all ends				
Connection	ı Туре:				
Flange all e	nds				
Valve Size:					
2.000 inche	s				
Maximum (	Operating Pressure:				
150.0 pound	ds per square inch single response				
Thickness:					
0.688 inche	s 2nd end				
First Connection Face To Centerline Distance:					
4.812 inche	s				
Bolt Hole D	Piameter:				
0.750 inche	s 2nd end				
Second Co	nnection Face To Centerline Distance:				
4.750 inche	s				
<b>Bolt Circle</b>	Diameter:				
6.000 inche	s 2nd end				
Flange Fac	e Design:				
Raised strai	ight 2nd end				
Raised Fac	e Height:				
0.062 inche	s 2nd end				
Raised Fac	e Diameter:				
5.000 inche	s 2nd end				
Material:					
Stainless st	eel stem				
Media For \	Which Designed:				
Air single re	sponse				
Style Desig	ınator:				
Err-090					

## NSN 4820-01-184-2732

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0