NSN 4820-01-184-3570

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-184-3570

Bolted
Bolt Hole Quantity:
3 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+15.0/+19.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.562 inches all ends
Face To Face Distance:
1.250 inches
Thickness:
0.375 inches all ends
First Connection Face To Centerline Distance:
3.094 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.094 inches
Bolt Circle Diameter:
2.438 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy body
coppor and sour
Media For Which Designed:
Media For Which Designed:
Media For Which Designed: Water-oil-gas single response

NSN 4820-01-184-3570

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0