## NSN 4820-01-184-5444

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

Bonnet Type: Inside screw

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-184-5444

Doiled
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
500.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+131.0/+150.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
4.250 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.250 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.250 inches
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel seat
Media For Which Designed:
Oil, hydraulic 1st response
Style Designator:
Err-090

## NSN 4820-01-184-5444

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0