## NSN 4820-01-184-9373

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-184-9373 Flow Control Device: Disk **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method: Bolted** Renewable Seat Ring Type: Threaded **Bolt Hole Quantity:** 12 all ends **Maximum Operating Temp:** 425.0 degrees fahrenheit single response **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal Valve Size: 6.000 inches **Maximum Operating Pressure:** 100.0 pounds per square inch single response **Outside Diameter:** 10.125 inches all ends Thickness: 0.562 inches all ends **First Connection Face To Centerline Distance:** 8.000 inches **Bolt Hole Diameter:** 0.688 inches all ends **Second Connection Face To Centerline Distance:** 8.000 inches **Bolt Circle Diameter:** 8.875 inches all ends Flange Face Design: Plain all ends Material:

Media For Which Designed: Water-oil-gas single response

Copper alloy body

## NSN 4820-01-184-9373

Stop-check Valve - Page 2 of 2



| STV/IA | LIDEIG | natar. |
|--------|--------|--------|
| SIVIE  | Desig  | Halvi. |
|        |        |        |

Angle flanged ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0