NSN 4820-01-186-5981

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-186-5981

Threaded	
Bolt Hole Quantity:	
4 all ends	
Maximum Operating Temp:	
250.0 degrees fahrenheit single response	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
0.500 inches	
Adjustable Pressure Range:	
+59.0/+72.0 pounds per square inch	
Maximum Operating Pressure:	
400.0 pounds per square inch single response	
Outside Diameter:	
4.250 inches 1st end	
Thickness:	
0.375 inches 1st end	
First Connection Face To Centerline Distance:	
3.250 inches	
Bolt Hole Diameter:	
0.625 inches all ends	
Second Connection Face To Centerline Distance:	
3.312 inches	
Bolt Circle Diameter:	
3.125 inches 1st end	
Flange Face Design:	
Raised straight all ends	
Raised Face Height:	
0.062 inches all ends	
Raised Face Diameter:	
1.375 inches all ends	
Material:	
Stainless steel stem	

NSN 4820-01-186-5981

Safety Relief Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0