## NSN 4820-01-187-1962

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-187-1962

| Disk Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Bolted Bolt Hole Quantity: 8 all ends Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed: Oil, hydraulic 2nd response | Flow Control Device:                      |
|---|---|
| Outside screw-yoke Bonnet Attachment Method: Bolted Bolt Hole Quantity: 8 all ends Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:   | Disk                                      |
| Bonnet Attachment Method: Bolted Bolt Hole Quantity: 8 all ends Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:                      | Bonnet Type:                              |
| Bolted Bolt Hole Quantity: 8 all ends Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Face To Face Distance: 11.500 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Outside screw-yoke                        |
| Bolt Hole Quantity: 8 all ends Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:   | Bonnet Attachment Method:                 |
| Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Bolted                                    |
| Maximum Operating Temp:  425.0 degrees fahrenheit single response  Valve Operation Method:  Manual  Flange Shape: Round with holes all ends  Connection Type: Flange all ends  Mounting Position: Horizontal  Valve Size: 2.000 inches  Maximum Operating Pressure: 400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:  | Bolt Hole Quantity:                       |
| Valve Operation Method:  Manual Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 5.000 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | 8 all ends                                |
| Valve Operation Method:  Manual  Flange Shape: Round with holes all ends  Connection Type: Flange all ends  Mounting Position: Horizontal  Valve Size: 2.000 inches  Maximum Operating Pressure: 400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:   | Maximum Operating Temp:                   |
| Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | 425.0 degrees fahrenheit single response  |
| Flange Shape: Round with holes all ends Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Valve Operation Method:                   |
| Round with holes all ends  Connection Type: Flange all ends  Mounting Position: Horizontal  Valve Size: 2.000 inches  Maximum Operating Pressure: 400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:  | Manual                                    |
| Connection Type: Flange all ends Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Flange Shape:                             |
| Flange all ends  Mounting Position: Horizontal  Valve Size: 2.000 inches  Maximum Operating Pressure: 400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:  | Round with holes all ends                 |
| Mounting Position: Horizontal Valve Size: 2.000 inches Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:   | Connection Type:                          |
| Horizontal  Valve Size: 2.000 inches  Maximum Operating Pressure: 400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:  | Flange all ends                           |
| Valve Size:  2.000 inches  Maximum Operating Pressure:  400.0 pounds per square inch 2nd response  Outside Diameter:  6.500 inches all ends  Face To Face Distance:  11.500 inches  Thickness:  0.813 inches all ends  Bolt Hole Diameter:  0.750 inches all ends  Bolt Circle Diameter:  5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | Mounting Position:                        |
| 2.000 inches  Maximum Operating Pressure:  400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:   | Horizontal                                |
| Maximum Operating Pressure:  400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:   | Valve Size:                               |
| 400.0 pounds per square inch 2nd response  Outside Diameter: 6.500 inches all ends  Face To Face Distance: 11.500 inches  Thickness: 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:  | 2.000 inches                              |
| Outside Diameter: 6.500 inches all ends Face To Face Distance: 11.500 inches Thickness: 0.813 inches all ends Bolt Hole Diameter: 0.750 inches all ends Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Maximum Operating Pressure:               |
| 6.500 inches all ends  Face To Face Distance:  11.500 inches  Thickness:  0.813 inches all ends  Bolt Hole Diameter:  0.750 inches all ends  Bolt Circle Diameter:  5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | 400.0 pounds per square inch 2nd response |
| Face To Face Distance:  11.500 inches  Thickness:  0.813 inches all ends  Bolt Hole Diameter:  0.750 inches all ends  Bolt Circle Diameter:  5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:  | Outside Diameter:                         |
| Thickness:  0.813 inches all ends  Bolt Hole Diameter:  0.750 inches all ends  Bolt Circle Diameter:  5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | 6.500 inches all ends                     |
| Thickness:  0.813 inches all ends  Bolt Hole Diameter:  0.750 inches all ends  Bolt Circle Diameter:  5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | Face To Face Distance:                    |
| 0.813 inches all ends  Bolt Hole Diameter: 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material: Copper alloy body  Media For Which Designed:   | 11.500 inches                             |
| Bolt Hole Diameter:  0.750 inches all ends  Bolt Circle Diameter:  5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:  | Thickness:                                |
| 0.750 inches all ends  Bolt Circle Diameter: 5.000 inches all ends  Flange Face Design: Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | 0.813 inches all ends                     |
| Bolt Circle Diameter: 5.000 inches all ends Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Bolt Hole Diameter:                       |
| 5.000 inches all ends  Flange Face Design:  Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | 0.750 inches all ends                     |
| Flange Face Design: Plain all ends Material: Copper alloy body Media For Which Designed:  | Bolt Circle Diameter:                     |
| Plain all ends  Material:  Copper alloy body  Media For Which Designed:   | 5.000 inches all ends                     |
| Material: Copper alloy body Media For Which Designed:   | Flange Face Design:                       |
| Copper alloy body  Media For Which Designed:  | Plain all ends                            |
| Media For Which Designed:   | Material:                                 |
| _   | Copper alloy body                         |
| Oil, hydraulic 2nd response   | Media For Which Designed:                 |
|   | Oil, hydraulic 2nd response               |
| Style Designator:   | Style Designator:                         |
| Straight through flanged ends   | Straight through flanged ends             |
| Shelf Life:   | Shelf Life:                               |
| N/a   | N/a                                       |

## NSN 4820-01-187-1962

Stop-check Valve - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A530b0