## NSN 4820-01-188-1781

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-188-1781

Disk						
Bonnet Type:						
Inside screw						
Bonnet Attachment Method:						
Bolted						
Disk Loading Method:						
Spring						
Bolt Hole Quantity:						
4 all ends						
Maximum Operating Temp:						
250.0 degrees fahrenheit single response						
Valve Operation Method:						
Automatic or manual						
Flange Shape:						
Round with holes all ends						
Connection Type:						
Flange all ends						
Valve Size:						
1.000 inches						
Adjustable Pressure Range:						
+10.0/+12.0 pounds per square inch						
Maximum Operating Pressure:						
400.0 pounds per square inch single response						
Outside Diameter:						
4.250 inches all ends						
Thickness:						
0.438 inches all ends						
First Connection Face To Centerline Distance:						
4.250 inches						
Bolt Hole Diameter:						
0.562 inches all ends						
Second Connection Face To Centerline Distance:						
4.250 inches						
Bolt Circle Diameter:						
3.125 inches all ends						
Flange Face Design:						
Plain all ends						
Style Designator:						
Err-090						
Shelf Life:						
N/a						

## NSN 4820-01-188-1781

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0