## NSN 4820-01-188-5834

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-188-5834

| Flow Control Device:  |
|---|
| Disk  |
| Bonnet Type:  |
| Inside screw  |
| Bonnet Attachment Method:   |
| Union   |
| Bolt Hole Quantity:   |
| 4 all ends  |
| Maximum Operating Temp:   |
| 500.0 degrees fahrenheit 1st response                               |
| Valve Operation Method:   |
| Manual  |
| Flange Shape:   |
| Round with holes all ends   |
| Connection Type:  |
| Flange all ends   |
| Features Provided:  |
| Bonnet packing  |
| Valve Size:   |
| 3.000 inches  |
| Maximum Operating Pressure:   |
| 225.0 pounds per square inch 2nd response                           |
| Outside Diameter:   |
| 7.500 inches all ends   |
| Face To Face Distance:  |
| 6.938 inches  |
| Thickness:  |
| 0.625 inches all ends   |
| Bolt Hole Diameter:   |
| 0.750 inches all ends   |
| Bolt Circle Diameter:   |
| 6.000 inches all ends   |
| Flange Face Design:   |
| Plain all ends  |
| Material:   |
| Plastic polytetrafluoroethylene packing                             |
| Material Specification:   |
| Astm b61 assn standard single material response flow control device |
| Media For Which Designed:   |
| Water-oil-gas 2nd response  |
| Style Designator:   |
| Err-090   |

## NSN 4820-01-188-5834

Globe Valve - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0