

View Online at <https://aerobasegroup.com/nsn/4820-01-189-7581>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange all ends

Valve Size:

4.000 inches

Adjustable Pressure Range:

+72.0/+88.0 pounds per square inch

Maximum Operating Pressure:

3300.0 pounds per square inch single response

Outside Diameter:

9.000 inches 2nd end

Thickness:

1.250 inches 2nd end

First Connection Face To Centerline Distance:

8.438 inches

Bolt Hole Diameter:

0.875 inches 1st end

Second Connection Face To Centerline Distance:

8.500 inches

Bolt Circle Diameter:

9.500 inches 1st end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.062 inches 2nd end

Raised Face Diameter:

6.188 inches 2nd end

Special Features:

Spring material corrosion resistant steel astm a313 (std)

Material:

Stainless steel stem

Media For Which Designed:

Liquid, ingested single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0