

View Online at <https://aerobasegroup.com/nsn/4820-01-189-8516>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

550.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.500 inches

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.500 inches

Thickness:

0.688 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

4.125 inches all ends

Material:

Plastic polytetrafluoroethylene packing

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 12168 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0