

View Online at <https://aerobasegroup.com/nsn/4820-01-190-7086>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Bolt Hole Quantity:

12 all ends

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 1st end

Connection Type:

Flange all ends

Valve Size:

6.000 inches

Adjustable Pressure Range:

+65.0/+100.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

12.500 inches all ends

Thickness:

1.188 inches all ends

First Connection Face To Centerline Distance:

8.500 inches

Bolt Hole Diameter:

0.875 inches 1st end

Second Connection Face To Centerline Distance:

10.000 inches

Bolt Circle Diameter:

10.625 inches all ends

Flange Face Design:

Plain all ends

Material:

Bronze bodyrubber flow control devicenickel alloy stem

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0