NSN 4820-01-192-3478

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-192-3478



Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.500 inches

Adjustable Pressure Range:

+18.0/+22.0 pounds per square inch

Maximum Operating Pressure:

400.0 pounds per square inch single response

Outside Diameter:

3.500 inches all ends

Thickness:

0.375 inches all ends

First Connection Face To Centerline Distance:

3.312 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

3.312 inches

Bolt Circle Diameter:

2.438 inches all ends

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

NSN 4820-01-192-3478

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0