NSN 4820-01-192-3478

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-192-3478

31	
Outside screw-yoke	
Bonnet Attachment Method:	
Bolted	
Bolt Hole Quantity:	
4 all ends	
Maximum Operating Temp:	
250.0 degrees fahrenheit single response	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
0.500 inches	
Adjustable Pressure Range:	
+18.0/+22.0 pounds per square inch	
Maximum Operating Pressure:	
400.0 pounds per square inch single response	
Outside Diameter:	
3.500 inches all ends	
Thickness:	
0.375 inches all ends	
First Connection Face To Centerline Distance:	
3.312 inches	
Bolt Hole Diameter:	
0.562 inches all ends	
Second Connection Face To Centerline Distance:	
3.312 inches	
Bolt Circle Diameter:	
2.438 inches all ends	
Flange Face Design:	
Plain all ends	
Material:	
Stainless steel stem	
Media For Which Designed:	
Water-oil-gas single response	
Style Designator:	
Err-090	

NSN 4820-01-192-3478

Safety Relief Valve - Page 2 of 2



F	urnished	Items	And	Quantity	/ :
1	lever				

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0