NSN 4820-01-192-9562

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-192-9562



Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Threaded

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.500 inches

Adjustable Pressure Range:

+71.0/+100.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

3.500 inches all ends

Thickness:

0.438 inches all ends

First Connection Face To Centerline Distance:

3.250 inches

Bolt Hole Diameter:

0.500 inches all ends

Second Connection Face To Centerline Distance:

3.125 inches

Bolt Circle Diameter:

2.375 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.375 inches all ends

Material:

Steel body

NSN 4820-01-192-9562

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Water, fresh single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0