NSN 4820-01-192-9563

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bolt Hole Quantity:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk

Bolted

4 all ends



View Online at https://aerobasegroup.com/nsn/4820-01-192-9563

Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+59.0/+72.0 pounds per square inch
Outside Diameter:
6.625 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
5.062 inches
Bolt Hole Diameter:
0.938 inches all ends
Second Connection Face To Centerline Distance:
5.062 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever

NSN 4820-01-192-9563

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0