NSN 4820-01-193-4647

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-193-4647

| Disk | |
|------------------------------------------------|--|
| Bonnet Type: | |
| Inside spring | |
| Bonnet Attachment Method: | |
| Bolted | |
| Disk Loading Method: | |
| Spring | |
| Bolt Hole Quantity: | |
| 4 all ends | |
| Valve Operation Method: | |
| Automatic | |
| Flange Shape: | |
| Round with holes all ends | |
| Connection Type: | |
| Flange all ends | |
| Valve Size: | |
| 1.000 inches | |
| Maximum Operating Pressure: | |
| 285.0 pounds per square inch single response | |
| Opening Pressure Setting: | |
| 101.0 pounds per square inch | |
| Outside Diameter: | |
| 4.250 inches all ends | |
| Thickness: | |
| 0.438 inches all ends | |
| First Connection Face To Centerline Distance: | |
| 4.125 inches | |
| Bolt Hole Diameter: | |
| 0.625 inches all ends | |
| Second Connection Face To Centerline Distance: | |
| 4.500 inches | |
| Bolt Circle Diameter: | |
| 3.125 inches all ends | |
| Flange Face Design: | |
| Raised straight all ends | |
| Raised Face Height: | |
| 0.062 inches all ends | |
| Raised Face Diameter: | |
| 2.000 inches all ends | |
| Material: | |
| Steel body | |
| | |

NSN 4820-01-193-4647

Safety Relief Valve - Page 2 of 2



| Style Designator: |
|-------------------|
| Err-090 |
| Shelf Life: |
| N/a |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0