## NSN 4820-01-197-3710

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-197-3710

Pipe Size Accommodated:
1.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Bolted
Maximum Operating Temp:
180.0 degrees fahrenheit single response
End Application:
Oliver hazard perry class ffg
Connection Style:
•
Socket with brazing ring err-100
Valve Operation Method: Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+30.0/+50.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Massura:

-

## NSN 4820-01-197-3710

Safety Relief Valve - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A046b0