NSN 4820-01-197-4747

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk

View Online at https://aerobasegroup.com/nsn/4820-01-197-4747



Threaded **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 400.0 degrees fahrenheit single response Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 0.500 inches Adjustable Pressure Range: +90.0/+110.0 pounds per square inch Maximum Operating Pressure: 275.0 pounds per square inch single response **Outside Diameter:** 4.250 inches 1st end Thickness: 0.438 inches all ends **First Connection Face To Centerline Distance:** 3.312 inches **Bolt Hole Diameter:** 0.500 inches all ends **Second Connection Face To Centerline Distance:** 3.250 inches **Bolt Circle Diameter:** 3.125 inches 1st end Flange Face Design: Raised straight all ends **Raised Face Height:** 0.062 inches all ends **Raised Face Diameter:**

2.000 inches 1st end

Material:

Stainless steel stem

NSN 4820-01-197-4747

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

