

01-198-2747

NSN 4820-01-198-2747 Safety Relief Valve - Page 1 of 2
 View Online at https://aerobasegroup.com/nsn/4820-0
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+8.0/+10.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.312 inches all ends
First Connection Face To Centerline Distance:
3.438 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.438 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Plain all ends

Material: Stainless steel stem

Media For Which Designed:

Water, fresh single response

NSN 4820-01-198-2747

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

