

View Online at <https://aerobasegroup.com/nsn/4820-01-198-6263>

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Piston

**Valve Discharge Flow Rate:**

2.0 gallons per minute

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**Connection Style:**

G4 gasket sea (boss) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded internal boss all ends

**Mounting Facility:**

Bracket

**Thready Qty Per Inch (tpi):**

3b all ends

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Thread Size:**

0.375 inches all ends

**Material:**

Steel comp 303 flow control device or steel comp 303se flow control device and steel comp 303 plus x flow control device

**Material Specification:**

Qq-a-225/9 alloy 7075 t73 federal specification single material response body

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 type 2, cl1 military specification single treatment response

**Style Designator:**

Err-090

**Thread Series Designator:**

Unjf all ends

**Specification Data:**

36659-672030 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.