NSN 4820-01-198-6263

Shuttle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-198-6263

Thread Class:
3b 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Piston
Valve Discharge Flow Rate:
2.0 gallons per minute
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Mounting Facility:
Bracket
Thready Qty Per Inch (tpi):
3b all ends
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Material:
Steel comp 303 flow control device or steel comp 303se flow control device and steel comp 303 plus x flow control device
Material Specification:
Qq-a-225/9 alloy 7075 t73 federal specification single material response body
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 type 2, cl1 military specification single treatment response
Style Designator:
Err-090
Thread Series Designator:
Unjf all ends
Specification Data:
36659-672030 manufacturers specification control
Shelf Life:

N/a

NSN 4820-01-198-6263

Shuttle Valve - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.