NSN 4820-01-198-8613

Check Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-198-8613

| Disk |
|--|
| Disk Loading Method: |
| Spring |
| Bolt Hole Quantity: |
| 4 all ends |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit single response |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal or vertical |
| Valve Size: |
| 3.000 inches |
| Outside Diameter: |
| 7.500 inches all ends |
| Face To Face Distance: |
| 3.125 inches |
| Thickness: |
| 0.625 inches all ends |
| Bolt Hole Diameter: |
| 0.625 inches all ends |
| Bolt Circle Diameter: |
| 6.000 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |
| Copper alloy |
| Media For Which Designed: |
| Water, fresh single response |
| Style Designator: |
| Straight through flanged ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 4820-01-198-8613

Check Valve - Page 2 of 2



Fiig:

A530b0