NSN 4820-01-200-1727

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-200-1727 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** G4 gasket sea (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Adjustable Pressure Range:** +240.0/+360.0 pounds per square inch **Maximum Operating Pressure:** 2500.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 37.0 degrees all ends **Opening Pressure Setting:** 300.0 pounds per square inch Material: Rubber butadiene-acrylonitrile class nbr seat Media For Which Designed: Ammonia, liquid 4th response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unjf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 4820-01-200-1727

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.