## NSN 4820-01-200-7056

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-200-7056

| View Online at https://aerobasegroup.com/nsn/4820-01-200-70 |
|---|
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Flow Control Device:  |
| Poppet  |
| Disk Loading Method:  |
| Spring  |
| Valve Discharge Flow Rate:                                  |
| 0.1 gallons per minute                                      |
| Connection Style:   |
| G50 external seat for gasket seal (boss) 1st end            |
| Valve Operation Method:                                     |
| Automatic   |
| Connection Type:  |
| Threaded external boss 1st end                              |
| Adjustable Pressure Range:                                  |
| +50.0/+1500.0 pounds per square inch                        |
| Maximum Operating Pressure:                                 |
| 1500.0 pounds per square inch single response               |
| Thread Size:  |
| 0.750 inches 1st end  |
| Material:   |
| Steel seat  |
| Media For Which Designed:                                   |
| Hydraulic fluid, petroleum base single response             |
| Style Designator:   |
| Err-090   |
| Thread Series Designator:                                   |
| Unf 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A046b0  |
|   |
|   |