## NSN 4820-01-200-8556

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-200-8556

1 low Control Device.
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
1.000 inches
Opening Pressure Setting:
448.0 pounds per square inch
Outside Diameter:
6.000 inches 1st end
Thickness:
0.688 inches 2nd end
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches 2nd end
Second Connection Face To Centerline Distance:
4.125 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
3.625 inches 1st end
Special Features:
With nozzle on inlet end
Material:
Stainless steel flow control device
Shelf Life:
N/a

## NSN 4820-01-200-8556

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0