## NSN 4820-01-204-7922

Gate Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-204-7922

Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Valve Operation Method: Manual Stem Type: Nonrising Criticality Code Justification: Zzzy Special Features: 1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14 Material:	
Bonnet Attachment Method: Threaded Valve Operation Method: Manual Stem Type: Nonrising Criticality Code Justification: Zzzy Special Features: 1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Threaded  Valve Operation Method:  Manual  Stem Type:  Nonrising  Criticality Code Justification:  Zzzy  Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Valve Operation Method:  Manual  Stem Type:  Nonrising  Criticality Code Justification:  Zzzy  Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Manual  Stem Type: Nonrising  Criticality Code Justification:  Zzzy  Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Stem Type: Nonrising Criticality Code Justification: Zzzy Special Features: 1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Nonrising  Criticality Code Justification:  Zzzy  Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Criticality Code Justification:  Zzzy  Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Zzzy  Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
Special Features:  1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
1st end connection, unthd internal pipe-size 1.250 in.; max operating temp 500 degrees f; max operating pressure 200 psi; valve pc 14, and nipple-detail 14	
pc 14, and nipple-detail 14	
	comes with
Material	
waterial.	
Stainless steel stem	
Reference Number Differentiating Characteristics:	
Material will be iaw ships parts control center activity hx quality control, manufacturing and testing specs	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A500a0	