NSN 4820-01-204-9475

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-204-9475

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Valve Size:
2.500 inches
Adjustable Pressure Range:
+929.0/+1010.0 pounds per square inch
Maximum Operating Pressure:
1480.0 pounds per square inch single response
Outside Diameter:
9.000 inches 1st end
Thickness:
0.875 inches 1st end
First Connection Face To Centerline Distance:
6.750 inches
Bolt Hole Diameter:
0.750 inches 2nd end
Second Connection Face To Centerline Distance:
6.125 inches
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
4.125 inches 2nd end
Material:
Stainless steel stem
Style Designator:
Err-090
Shelf Life:
N/a

N/a

NSN 4820-01-204-9475

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0