NSN 4820-01-206-4373

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-206-4373

| Flow Control Device: |
|---|
| Disk |
| Disk Loading Method: |
| Weight |
| Renewable Seat Ring Type: |
| Threaded |
| Bolt Hole Quantity: |
| 8 all ends |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal or vertical |
| Valve Size: |
| 8.000 inches |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 13.500 inches all ends |
| Face To Face Distance: |
| 19.500 inches |
| Thickness: |
| 1.063 inches all ends |
| Bolt Hole Diameter: |
| 0.875 inches all ends |
| Bolt Circle Diameter: |
| 11.750 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| 10.625 inches all ends |
| Special Features: |
| Swing-check type; end flange dimensions conform to ansi b16.5, face to face dimensions conform to ansi b16.10 |
| Material: |
| Steel uns j92800 body |
| Style Designator: |
| Straight through flanged ends |

NSN 4820-01-206-4373

Check Valve - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0