NSN 4820-01-207-7017

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-207-7017

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Maximum Operating Pressure:
285.0 pounds per square inch single response
Opening Pressure Setting:
56.0 pounds per square inch
Outside Diameter:
7.500 inches all ends
Thickness:
0.938 inches 1st end
First Connection Face To Centerline Distance:
6.500 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
6.500 inches
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
5.000 inches 2nd end

NSN 4820-01-207-7017

Safety Relief Valve - Page 2 of 2



ate		

Stainless steel stem

Media For Which Designed:

Air 1st response

Style Designator:

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0